

Polar®

Choice White

Polar® Choice White is the ideal choice for a printable monomeric PVC film. Available with a gloss or matte finish and permanent or removable adhesive, Polar® Choice White maximises adhesive performance on a wide variety of substrates.

Polar® Choice White is outdoor durable for up to 3 years and is ideal for signage and general advertising applications, including windows, POP displays, stickers and decals.

- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- WINDOW & WALL GRAPHICS
- SUITABLE FOR MANY APPLICATIONS

Product Codes:

CGWG - Polar Choice White Gloss PB

CPWG - Polar Choice White Gloss P

CRWM - Polar Choice White Matte RB

80
micron

White
Monomeric
PVC

Gloss or
Matte



(Eco)Solvent
Latex
UV



Permanent or Removable
Acrylic Solvent
Adhesive



Widths up to 1524mm



5 YEARS DURABILITY
INTERIOR & EXTERIOR
(unprinted)

THE CHOICE FOR MONOMERIC PVC



APPLICATIONS

GENERAL SIGNAGE

WINDOW GRAPHICS

EXHIBITION GRAPHICS

POS DISPLAY



 **colyer.**
repoint
PRINTERS | SUPPLIES | SUPPORT

Polar®

Choice White

TECHNICAL SPECIFICATION

Polar® Choice White films are 80µ (3.2 mil) gloss or matte white monomeric PVC films, coated on one side with a permanent or removable, pressure sensitive clear or grey solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner. Suitable for interior and exterior use (up to 5 years).

CGWG - Polar Choice White Gloss PB

White Gloss film with Permanent Grey Adhesive

CPWG - Polar Choice White Gloss P

White Gloss film with Permanent Clear Adhesive

CRWM - Polar Choice White Matte RB

White Matte film with Removable Grey Adhesive

IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS

SUITABLE FOR INTERIOR AND EXTERIOR USE

CAN BE APPLIED TO MANY SMOOTH SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	White Gloss or Matte Monomeric PVC
Adhesive	Clear or Grey Permanent or Grey Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	140gsm 2 side PE Coated Release Paper

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ) 4.2 mil
Adhesive Layer	1 mil (25µ) (105µ)
Outdoor Durability	5 Years (Unprinted)
Fire Rating (EN 13501-1)	Class B
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Choice, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Choice are Drytac's Dynamic™, Interlam™ or Protac™ overlaminates.

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500


PRINTERS | SUPPLIES | SUPPORT