

Polar®

Premium Clear Permanent

EXCELLENT PRINTING SURFACE

Polar® Premium is a phthalate-free polymeric PVC film that provides an excellent printing surface, as well as excellent indoor and outdoor durability. Polar® Premium Clear Permanent has a clear matte or gloss finish and a permanent clear adhesive. The high quality clear adhesive is ideal for a wide variety of substrates.

- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- SUITABLE FOR MANY APPLICATIONS
- CAN BE USED FOR VEHICLE LIVERY- FLAT OR SLIGHTLY CURVED SURFACES

Product Code: PCG & PCM

80
micron

Clear
Polymeric
PVC

Matte
or Gloss



(Eco)Solvent
Latex
UV



Clear
Permanent
Acrylic Adhesive



Widths up to 1524mm



7 YEARS DURABILITY
INTERIOR & EXTERIOR

(with matched overlamine)



APPLICATIONS

- GENERAL SIGNAGE
- WINDOW GRAPHICS
- EXHIBITION GRAPHICS
- POS DISPLAY

 **colyer.**
repopoint
PRINTERS | SUPPLIES | SUPPORT

Polar® Premium Clear is an 80µ (3.2 mil) premium, phthalate-free printable polymeric solvent self-adhesive PVC film with a high quality, clear acrylic adhesive. Polar® Premium provides a consistent printing surface. Available with a gloss or matte clear film with a clear permanent adhesive for optimum performance on a wide variety of substrates.

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE USED FOR VEHICLE LIVERY- FLAT OR SLIGHTLY CURVED SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Clear Gloss or Matte Polymeric PVC
Adhesive	Clear Permanent Solvent Acrylic Adhesive
Release Liner	140 gsm 2 Side PE Coated, 1 Side Siliconised White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)	4.2 mil (105µ)
Adhesive Layer	1 mil (25µ)	
Outdoor Durability	7 Years	
Fire Rating	Class C	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-22°F to 176°F (-30°C to 80°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

OVERLAMINATE RECOMMENDATIONS

When using Polar® Premium, an overlamine can be used for maximum life expectancy. Products recommended for use with Polar® Premium are Drytac's Weathershield™ laminating films.

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500