

Weathershield® Glossy is a 3.2 mil (80µ) polymeric calendared PVC laminating film with a gloss finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with siliconised PE.

- SUITABLE FOR OUTDOOR APPLICATIONS, INCLUDING BANNERS, VEHICLE GRAPHICS (FLAT OR CURVED SURFACES) AND COMMERCIAL SIGNS, AS IT OFFERS SUPERB CLARITY FOR COLOR OPTIMISATION
- WHEN MATCHED WITH A HIGH QUALITY, POLYMERIC PRINT MEDIA, WEATHERSHIELD® GLOSSY OFFERS ITS BEST LONG-TERM PERFORMANCE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

### PRODUCT STRUCTURE

<b>Film</b>	Gloss Polymeric Calendared PVC
<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated Siliconised Kraft Paper

### PRODUCT CHARACTERISTIC

<b>Film Weight</b>	3.2 mil (80µ)	4.1 mil (102µ)
<b>Adhesive Layer</b>	0.9 mil (22µ)	
<b>UV Protection Factor</b>	Yes	
<b>Outdoor Durability</b>	7 years	
<b>Fire Rating</b>	Class 0 (BS 476 Part 6 and 7)	
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)	
<b>Peel Strength (20 min, FTM1)</b>	15 N/25mm	
<b>Shelf Life</b>	2 years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500