

Datasheet

## **HP Latex 365 Printer**



Produce a wide range of outdoor and indoor applications with this full-feature 64-inch printer



# Expand your applications—beat client expectations

- Print on traditional signage substrates and beyond—up to 64 inches—print textiles with the ink collector.<sup>1</sup>
- Reach more indoor spaces, like healthcare water-based HP Latex Ink prints are odorless.<sup>1</sup>
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi.

# Same day delivery—for highly demanding turnarounds

- High quality at high speeds—334 ft²(31 m²)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer.<sup>3</sup>
- Reach production speeds and avoid wait time prints come out completely dry and ready to finish and deliver.
- Gain productivity—reduce time between jobs with continuous printing.
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner.<sup>2</sup>

### Keep your running costs low—boost your capacity

- Increase production time and reduce time monitoring the printer—automatic, reliable, lowmaintenance printing.
- Save time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic.<sup>4</sup>
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads.
- Monitor your printer remotely with the free HP Latex Mobile app.<sup>5</sup>

For more information, please visit http://www.hp.com/go/latex365

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

<sup>&</sup>lt;sup>1</sup> Performance may vary depending on media—for more information, see http://www.hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles. Odorless prints: there is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>&</sup>lt;sup>2</sup> Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.

3 Banner-quality prints in outdoor (A-pass A-color) mode.

<sup>&</sup>lt;sup>3</sup> Banner-quality prints in outdoor (4-pass 4-color) mode. <sup>4</sup> ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

S HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

### **Technical specifications**

Print	
Printing modes	91 m²/hr - Max Speed (1 pass) 31 m²/hr - Outdoor High Speed (4 pass) 23 m²/hr - Outdoor High Speed (4 pass) 17 m²/hr - Indoor Quality (8 pass) 17 m²/hr - Indoor Quality (8 pass) 14 m²/hr - Indoor High Quality (10 pass) 6 m²/hr - Backlits, Textlies, and Carvas (16 pass) 5 m²/hr - High Saturation Textlies (20 pass)
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	7 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer)
Cartridge size	775 ml
Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)
Long-term print-to-print repeatability	Average ≤ 1 dE2000, 95% of colors ≤ 2 dE2000 <sup>1</sup>
Media	
Handling	Roll feed, take-up reel, automatic cutter (for vinyl, paper-based media, backlit polyester film)
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fabrics, mesh, textiles <sup>2</sup>
Roll size	254 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Roll weight	42 kg
Roll diameter	250 mm
Thickness	Up to 0.5 mm
Applications	Banners; Displays; Double-sided banners; Exhibition and event graphics; Exterior signage; Indoor posters; Interio decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Traffic signage
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d	xh)
Printer	2561 x 840 x 1380 mm
Shipping	2795 x 760 x 1250 mm
Operating area	2761 x 1840 mm
Weight	
Printer	216 kg
Shipping	303.5 kg
What's in the box	HP Latex 365 Printer, printheads, maintenance cartridge, ink collector, output platen protector, printer stand, spindle, take-up reel, variable front tension kit, loading accessory, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords
Environmental ran	ges
Operating temperature	15 to 30°C
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep)
Sound power	7.4 B(A) (operating), 5.7 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	4.6 kW (printing), 85 W (ready), <2.5 W (sleep)
Requirements	Input voltage (auto ranging) 200-240 V ( $\pm$ 10%) two wires and PE; 50/60 Hz ( $\pm$ 3 Hz); two power cords; 16 A max per power cord
Certification	
Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
Environmental	ENERGY STAR; WEEE; RoHS (EU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Bronze; OSHA; CE marking
	compliant

**Ordering information** 

HP Latex 365 Printer

### Product V8L39A

Accessories	
FOM56A	HP Series 300 64-in Printer 2-in Spindle
F0M58A	HP Series 300 64-in Printer 3-in Spindle
F0M59A	HP Latex User Maintenance Kit
F0M63A	HP Series 300 Media Loading Accessory
F0M64A	HP Series 300/500 Edge Holder Kit
T4E58B	HP Latex Media Saver Kit
T7U74A	HP Series 300/500 Ink Collector Foam Kit

#### Original HP printing supplies

CZ677A	HP 831 Cyan/Black Latex Printhead	
CZ678A	HP 831 Yellow/Magenta Latex Printhead	
CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
CZ680A	HP 831 Latex Optimizer Printhead	
CZ681A	HP 831 Latex Maintenance Cartridge	
CZ688A	HP 831B 775-ml Black Latex Ink Cartridge	
CZ689A	HP 831B 775-ml Cyan Latex Ink Cartridge	
CZ690A	HP 831B 775-ml Magenta Latex Ink Cartridge	
CZ691A	HP 831B 775-ml Yellow Latex Ink Cartridge	
CZ692A	HP 831B 775-ml Light Cyan Latex Ink Cartridge	
CZ693A	HP 831B 775-ml Light Magenta Latex Ink Cartridge	
CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	

#### Original HP large format printing materials

HP Permanent Gloss Adhesive Vinyl (REACH certified<sup>3</sup>) HP Backlit Polyester Film<sup>4</sup> HP PVC-free Durable Smooth Wall Paper (REACH<sup>3</sup>, FSC<sup>®5</sup>, UL GREENGUARD GOLD certified<sup>6</sup>) HP Premium Poster Pape<sup>4</sup> (FSC<sup>®</sup> certified<sup>5</sup>)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com

#### Service and Support

U9JE3E HP 2 year NBD with Defective Media Retention U9JEEH F1 3 year NBD with Defective Media Retention
U9JE7 HF1 3 year NBD with Defective Media Retention
U9JE7 HF1 1 year Post Warranty NBD with Defective Media Retention
U9JE8 HF1 2 year Post Warranty NBD with Defective Media Retention

#### ECO highlights

- Better for printing companies/operators—no special ventilation or HAPs<sup>1</sup>
  Better for the end-customer, more differentiation—odorless prints reach more indoor
- Better for the environment—HP designs end-to-end sustainability into large-format printing
  HP Latex lnks are UL GREENGUARD GOLD Certified<sup>3</sup>

### Please recycle printing hardware and eligible printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

1 Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous kir Pollutants according to EPA Method 311.

2 There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

the odor performance of the final print.

3 UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULs GREENGUARD Standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org.

4 ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT registered where applicable/supported. See http://www.epeat.net for registration status by country.

Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.
Performance may vary depending on media—for more information, see http://www.hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The optional ink collector is required for porous textiles.

This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

HP Large Format Media take-back program availability varies. Some recyclable HP papers

Hinting Products and Consumable Supplies.

HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are available in all tentions.

all regions.  $^6$  UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage For more information, visit http://www.ul.com/gg or http://www.greenguard.org.

For more information, contact your HP Amplify Synergy Partner...



hello@colyer.co.uk | 01483 596200 | www.colyer.co.uk















