Xerox[®] AltaLink[®] Colour Multifunction Printers



Xerox[™]

C8130/C8135/C8145/C8155/C8170



Xerox[®] AltaLink[®] C8100 Series Colour Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.co.uk**.

System Specification	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170		
Speed ¹							
Colour/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm		
Monthly Duty Cycle ²	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages		
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ Optio	nal: 500 GB HDD/Intel Atom®	Quad Core 1.91 GHz/4 GB syste	em memory (8 GB system mem	ory AltaLink® C8170)		
Connectivity	Ethernet 10/100/1000 Base-7	Г, High-speed USB 2.0 direct pr	int, NFC, Optional: WiFi/WiFi D	irect with Xerox® Dual Band Wi	reless Kit, Bluetooth (iBeacon)		
Controller Features	Unified Address Book, Remote	Control Panel, Configuration C	Cloning, Fleet Orchestrator, Conf	îguration Watchdog			
Optional Controller	Xerox [®] EX-c C8100 Print Serve	er Powered by Fiery®					
Copy and Print							
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; P	rint: Up to 1200 x 2400 dpi					
First-Print-Out Time (as fast as)	5.7 seconds colour/4.2 second	ds black and white	4.9 seconds colour/ 3.8 seconds black and white	4.5 seconds colour/ 3.2 seconds black and white	3.8 seconds colour/ 3.0 seconds black and white		
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.1 seconds colour/4.5 seconds black and white		5.5 seconds colour/ 4.4 seconds black and white	4.7 seconds colour/ 3.7 seconds black and white	4.0 seconds colour/ 3.2 seconds black and white		
Page Description Language	Adobe [®] PostScript [®] 3™, Adobe	e [®] PDF, PCL [®] 5c/PCL [®] 6					
Print Features	Identification, Booklet Layout Printing (as default), Hold All	, Store and Recall Driver Setting Jobs, Long Sheet (Banner) Print	eDrive, and Google Drive), Enci 35, Bi-directional Real-time Statu ing, Print Around, Print on Alterr from and Scan to Xerox® DocuS	us, Scaling, Job Monitoring, App nate Paper; Imaging Security w	lication Defaults, Two-sided ith AltaLink's proprietary		
Mobile and Cloud Ready							
Mobile Connectivity	Near Field Communication (N	IFC); Optional: Wi-Fi Direct, Wi	i-Fi (802.11 b/g/n/ac), AirPrint (i	iOS) including iBeacon (Bluetoc	th)		
Mobile Printing		Mopria [®] Scan, Apple AirPrint [™] , Xerox [®] Print Service (Android), @PrintByXerox App; Optional: Xerox [®] Workplace Mobile App (iOS/Android), AirPrint [™] (iOS) including iBeacon (Bluetooth)					
Mobile Scanning	Mopria® Scan, Apple AirPrint™	, Optional: Xerox® Workplace	Mobile App (iOS/Android)				
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalise, print, convert, route, collaborate and communicate. Visit www.xerox.co.uk/en-gb/office/print-management-solutions to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.co.uk/ecm), XMPie [®] (www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised- communication-software), Xerox [®] Workplace Solutions (www.xerox.co.uk/en-gb/office/print-management-solutions)						
Xerox® Workplace Central Platform	cloud-based workflows you ca shareability with a wider audi	in change documents into audi	omputers, mobile devices and p o files for easy listening, conver ible, editable and shareable tex y set words or phrases	t PDF or image files to popular I	Vicrosoft formats for		

Xerox [®] Workplace Suite and Xerox [®] Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud-based-version (Workplace Cloud) of this solution.
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop or mobile login credentials to log in to your AltaLink® multifunction printers with direct connections to popular cloud identity providers Okta, Ping Identity and Microsoft® Azure
Scan	
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password-protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support, Touchless Workflow Accelerators, Imaging Security with AltaLink's proprietary marking and infrared detection technology
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at www.xerox.co.uk/en-gb/office/printer-software, Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, Firmware Verification, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager, LogRhythm SIEM, Splunk SIEM, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TL51.1/1.2/1.3, Security Certificates utilising ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2.User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Job Level Encryption via HTTPS and Drivers, Email, Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print, Imaging Security (copy, print, scan, email) with AltaLink's proprietary marking and infrared detection technology
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) ³ , Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with multi-pass Image optional hard drive, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at www.xerox.co.uk/en-gb/office/print-management-solutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at www.xerox.co.uk/en-gb/office/printer-software#printmanagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).





USER INTERFACE



Intuitive Tablet-like 10.1-inch Colour Touchscreen is customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

INNOVATIVE TECHNOLOGIES





Xerox[®] Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.

Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile devices to the AltaLink® C8100 Series user panel and quickly connect with the multifunction printer.

Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

PAPER INPUT⁴

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



High-Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four-Tray Module Configuration (available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1 320 mm.



High Capacity Feeder (optional) holds 3,000 sheets of A4 paper, increasing the maximum paper capacity to 6,140 sheets.

E

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 320 x 1,320 mm media.





PAPER OUTPUT/FINISHERS⁴

Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50-sheets of 75 gsm media.

Device Specification	
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic
Accessories	
Optional	BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Booklet Maker for Office Finisher Bluetooth Kit Convenience Stapler (includes Work Surface ⁵) Envelope Tray (Replaces Tray 1) Foreign Device Interface (also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and card readers High-Capacity Feeder 3000 A4 Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® C8130, C8135, C8145, C8155) Long Sheet Feed Kit (banner printing) McAfee [®] Integrity Control Enablement Kit Multi-feed Detection Kit (AltaLink® C8170 only) Office Finisher Smart Card Enablement Kit ³ Scan To Cloud Enablement Kit USB Keyboard/Shelf Kit Unicode Font Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Xerox [®] Ex-c C8100 Print Server Powered by Fiery [®] Xerox [®] Integrated RFID Card Reader Kit 500B HDD
Electrical Requirements	AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C8170
North America	Voltage: 110-127 VAC +/- 10% Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10% Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A Frequency: 50/60 Hz +/- 3%, 10 A

Device Specification (conti	nued)							
Power Consumption	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170			
Running (Average)	115V: 576 watts 230V: 586 watts	115V: 600.3 watts 230V: 595.8 watts	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts			
Standby Mode	115V: 67 watts 230V: 71 watts	115V: 64 watts 230V: 70 watts	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts			
Auto Off/Sleep Mode	115V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)			
Warm-up (from Off)	As fast as 8.5 seconds							
Recovery from Sleep	As fast as 4.5 seconds	ast as 4.5 seconds						
Operating Environment								
Required Temperature Range	10 to 28° C							
Required Relative Humidity	15% to 85%							
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 4.0/4.0 dB(A)							
Dimensions and Weight			1					
Base Configuration	Width: 620mm Depth: 723mm Height: 1,130mm Weight: 143.1kg				Width: 620mm Depth: 793mm Height: 1,169mm Weight: 159.7kg			
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 819 mm Depth: 723 mm Height: 1,130 mm Weight: 154.2 kg				N/A			
With Office Finisher (with Booklet Maker)	Width: 1,207mm Depth: 723mm Height: 1,130mm Weight: 182.5kg				Width: 1207mm Depth: 793mm Height: 1,169mm Weight: 199kg			
Base Configuration with Business Ready (BR) Finisher	Width: 1,395mm Depth: 723mm Height: 1,130mm Weight: 187kg				Width: 1,395mm Depth: 723mm Height: 1,169mm Weight: 203.4kg			
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm Depth: 723 mm Height: 1,130 mm Weight: 204 kg				Width: 1,496.3 mm Depth: 723 mm Height: 1,169 mm Weight: 220.6 kg			
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 1,632mm Depth: 723mm Height: 1,130mm Weight: 254.3kg				Width: 1,632mm Depth: 723mm Height: 1,169mm Weight: 270.9kg			
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 2,361mm Depth: 723mm Height: 1,130mm Weight: 285.2kg				Width: 2,361mm Depth: 723mm Height: 1,169mm Weight: 302kg			
System Certifications/Regu	latory Compliance				·			
Certifications	To view the latest list of certifi	cations, go to xerox.com/Offic	eCertifications					
	l				·			

Paper Handling	AltaLink [®] C8130	AltaLink® C8135	AltaLink [®] C8145	AltaLink® C8155	AltaLink [®] C8170	
	। atic Document Feeder (DADF))				
Capacity ⁴	130 sheets				250 sheets	
Speed (Up to)		82 ppm black-and-white and colour (simplex) 141 ipm black-and-white and colour (duplex) 270 ipm and colo				
Paper Sizes Sensed	85 x 125 mm to 297 x 432 m	IM				
Weights	60 to 128 gsm					
Bypass Tray (Standard)						
Capacity ⁴	100 sheets					
Sizes	Custom Sizes: 89 x 98 mm to	o 320 x 1320 mm (SEF); O J	btional: Long Sheet Feed Kit (I	Banner Printing)		
Weights	52 to 300 gsm, Long sheets/	/banners (>483 mm): 106	- 220 gsm			
	Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Relo Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Card Stock Reloa Lightweight Glossy Card Stocl Plain Plain-Reloaded Preprinted Recycled Transparencies Long Sheets/Banners: Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock	ck ck Reloaded ded k k Reloaded				
Trays 1 and 2 (Standard)	Eightweight eard stock heida					
Capacity ⁴	520 sheets each					
Sizes	Tray 1: Custom Sizes: 140 x 1 Tray 2: Custom Sizes: 140 x 1		SEF)			
Weights	52 to 300 gsm					
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloa Heavyweight Card Stock Reloa Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stocl Plain-Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded k				

Paper Handling (continued)	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170			
	 and 4) (Available on C8130/C	8135)						
Capacity ⁴	Tray 3: 520 sheets Tray 4: 520 sheets							
Sizes	Trays 3 and 4: 140 x 182 mm	n to SRA3 mm (SEF)						
Weights	52 to 300 gsm							
Media Types	Heavyweight Glossy Card Stor Heavyweight Glossy Card Stor Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloa Lightweight Glossy Card Stock	Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Lobels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted						
High Capacity Tandem Tra	y (Available with all models)							
Capacity ⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets							
Sizes	A4, JIS B5, Executive LEF							
Weights	52 to 300 gsm							
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted	Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain						
Envelope Tray (Optional –	Replaces Tray 1)							
Capacity ⁴	Up to 60 envelopes							
Sizes	No. 10 Commercial (235 x 10 Custom Sizes: 98 x 148 mm te							
Weights	75 to 90 gsm							
High-Capacity Feeder (HCF	;) (Optional with all models)							
Capacity ⁴	3,000 sheets							
Sizes	Standard Sizes: A4 or B5 LEF	Standard Sizes: A4 or B5 LEF						
Weights	52 to 300 gsm							
Total Capacity								
Device Total Capacity ⁴	Four Tray Module: 2,180 shee Four-Tray Module with High-C High-Capacity Tandem Tray N High-Capacity Tandem Tray N	Capacity Feeder: 5,180 sheet Aodule: 3,140 sheets						

Finishing	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170			
Output Trays (Standard) (E	ual Offset Catch Trays not a	vailable with Integrated (Office Finisher and limited t	o one with Office Finisher an	d BR Finishers)			
Stacking Tray Capacity ⁴		Dual Offset Catch Tray: Up to 250 sheets each eft Side Face-up Tray: Up to 100 sheets						
Integrated Office Finisher	Optional with AltaLink® C81	30/C8135/C8145/C8155)						
Stacking Tray Capacity ⁴	500 sheets of 80 gsm – A4 o	sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3						
Sizes	89 x 98 mm to 297 x 432 mr	n						
Weights	52 to 300 gsm							
Stapling								
Office Finisher (Optional)								
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,0	000 sheets single-stapled or	750 sheets dual-stapled (A4)					
Stacking Tray Sizes	210 x 182 mm to 297 x 432	mm						
Weights	52 to 300 gsm							
Multiposition Stapling	50 sheets maximum: A4/B5 s 30 sheets maximum: Legal/T			n covers)				
Hole Punch (Optional)	North America: 2/3-hole pu Europe: 2/4-hole punch Optional: 4-hole "Swedish" p							
Booklet Maker for Office Fi	nisher (Score/Crease, Saddle	-stitch Staple) (Optional)						
Top Tray Capacity ⁴	40 booklets (2-15 sheets per	booklet – 80 gsm or less)						
Sizes	Letter – A4 SEF Legal – B4 SEF Tabloid – A3 SEF							
Saddle-Stitch Stapling	2-15 sheets/8-60 page bookl 60 to 256 gsm	et						
Score/Crease	1-15 sheets/unstapled 60 to 105 gsm							
Business Ready (BR) Finish	er (Optional) (Requires Horiz							
Capacity ⁴	Offsetting Top Tray: 500 shee Stacking Stapling Tray: 3,000 100 sets (dual or 4-position s	sheets unstapled or	gle-position staple) A4					
Sizes	100 x 148 mm x 320 x 488 n 182 x 203 mm to 320 x 488 B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stap Auto stapling (50 sheets max		al, Tabloid, A3, A4, B4 and B5	sizes supported				
Hole Punch	North America: 2/3-hole pu Europe: 2/4-hole punch Optional: 4-hole "Swedish" p							
BR Booklet Maker Finisher	(Optional) (Requires Horizon	tal Transport Kit)						
Capacity"	Offsetting Top Tray: 500 shee 1,500 sheets of A4/A3 unsta 200 stapled sets of A4 (single	pled or		apled sets of A3				
Sizes	100 x 148 mm x 320 x 488 n 182 x 203 mm to 320 x 488 B5 to A3 for stapling							
Weights	52 to 300 gsm							
Stapling	Single and multiposition stap Auto stapling (50 sheets max		al, Tabloid, A3, A4, B4 and B5	sizes supported				
Hole Punch	North America: 2/3-hole pu Europe: 2/4-hole punch Optional: 4-hole "Swedish" p							
Booklet maker	Saddle-stitch 2 to 16 sheets (Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 s	5	coated or 5 sheets at 177 to	220 gsm coated)				

Finishing (continued)	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170				
C-fold/Z-fold Unit (Option	ا al with BR Finisher and BR ا	Booklet Maker Finisher)							
Types	C-fold, Z-fold, and Z-half-fo	C-fold, Z-fold, and Z-half-fold							
Capacity ⁴	40 sheets	40 sheets							
Sizes		C-fold and Z-fold: Letter – A4 SEF only Z-half-fold: Tabloid – A3 only							
Weights	64 to 90 gsm								
Output Trays	Envelope Tray: C-fold, Z-fol Stacker Tray or Top Tray: Z-								
Convenience Stapler (Opti	onal - Includes Work Surfac	:e ⁵)							
Capacity ⁴	50-sheet stapling 5,000 staples Requires separate power of								
Сору	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170				
First-Copy-Out Time (from platen/warmed up Colour/Black-and-White)	As fast as 6.1 seconds/ As fast as 4.5 seconds		As fast as 5.5 seconds/ As fast as 4.4 seconds	As fast as 4.7 seconds/ As fast as 3.7 seconds	As fast as 4.0 seconds/ As fast as 3.2 seconds				
Sides (input-output)	1-1, 1-2, 2-2, 2-1								
Quantity	1 to 9,999								
Resolution (max)	Up to 600 x 600 dpi								
Reduction/Enlargement	Variable zoom from 25% t	o 400% in 1% increments							
Concurrency	Program ahead to allow a	job to be queued while the in	itial job is processed (Copy, Print,	Fax and Scan)					
Copy Features	Authentication for Services Auto Paper Select Auto Reduction & Enlarger Auto Tray Switching Automatic 2-sided/Duplex Build Job (enables page-lee Collation Covers (front only, front an Dividers (blank) Edge Erase	nent (to fit the selected paper Booklet Creation vel programming and also let: d back, back only, printed insi at and graphic descriptions) s tre option) mirror image) s by 15 rows)	r size) s you proof each section or delet	e the last section as the job is b	uilt)				

Print	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170				
Resolution (up to)	1200 x 2400 dpi								
Print Features	Delay Print (specific time) Finishing Fit to New Paper Size Hold All Jobs Image Options (Toner Sar Imaging Security Job Identification (Print II LAN Fax (requires option Layout/Watermark Long Sheet/Banner N-up (up to 16 pages per Paper Selection by Attribu Print From Cloud Reposite Saved Job (colour jobs ca Secure Print with Timed D Special Pages (exception Store and Recall Driver Se	Colour by Words) Bi-directional User Permissions ver, Resolution (Standard, Enha D or Banner, Print ID in margin al Fax Kit) sheet) ute Sample Set ories (Dropbox, OneDrive and C n be printed as monochrome) Deletion page programming: covers, ins ttings erox® Earth Smart Settings, Du	anced, High)) s on first page only or all pages Google Drive) serts, exception pages)) 1 Print ID, Smart Sample Set, Ha	old All Jobs)				
Print from USB									
Operating Systems	Windows Server 2008 SP. Windows Server 2012 am Windows Server 2012 am Windows Server 2016 (64 Windows Server 2019 (64 Windows 7 (32- and 64-b Windows 8 (32- and 64-b Windows 8 (32- and 64-b Windows 10 (32- and 64- Mac OS 10.13, 10.14, 10. Fedora® Core Ubuntu®	(64-bit) d R2 (64-bit) 4-bit) 4-bit) iit) -bit) -bit) -bit)							
Network Protocols	TCP/IP: HTTP/HTTPS, Inte Microsoft Windows Netw Bonjour®/AirPrint™ IPv6 Most protocols not in use	orking over IP	D, Raw Socket Printing/Port 910	0, IPv4/IPv6, WSD					
Font Capability	PCL: 93 scalable fonts, lin	e printer and bitmap font (incl	uding Cyrillic font support) Post	Script 3: 173 Type 1 fonts, 2 Mu	Itiple Master fonts				
Xerox® Globαl Print Driver®				rox® Devices and non-Xerox dev ort calls and simplifying print se	vices from a single driver. It rvices management. Support for				
Xerox [®] Pull Print Driver	single driver. The Xerox® F	Pull Print Driver extends conver		printing assets. IT administrato	nment. Uses a single queue and rs no longer need to manage and				
Unified Address Book for F	Unified Address Book for Fax, Internet Fax, Email and Scan to								
Features	Maximum contacts: 5,000 Contacts: Supports 1 or m								

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink [®] C8170			
Concurrency	Scan while the system is concurrent jobs)	Scan while the system is printing, copying or while it is transferring scan-to-network or fax jobs (priority is for the return of scanned originals and printing concurrent jobs)						
Input Speed (up to)	82 ppm black-and-white 141 ipm black-and-white				135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)			
Resolution	72 x 72 dpi to 600 x 600) dpi						
Bit Depth	1-bit (black-and-white), 8	8-bit (greyscale), 24-bit (colour)						
Maximum Scan Area	A3							
Scan Template Management	Support 250 scan temple Create Xerox® CentreWa	ates ıre® IS scan templates and shar	e via device cloning to other mi	ultifunction printers' confirmat	ion sheet options			
Network Protocols	SFTP, FTP, SMB, HTTP, H	TTPS						
File Compression	Black-and-white TIFF (G Searchable PDF/OCR and	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearised PDF/PDF/A						
Document Management Fields (Metadata)	• 1 to 6 user-programma name, default value ar		k scan to file templates and un	limited fields within the templo	ate – Metadata field consists of field			
Scan Features	Auto Background and Sh Bound Originals Compression Quality/File Edge Erase Imaging Security Mixed Size Originals Scar Original Type (Photo and Reduction/Enlargement Scan Preview Single Touch Scan buttor Size for Size (for mixed-s Touchless Workflow Acce TWAIN Support/WIA 2.0	e Size Control n Build Job 1 Text, Photo, Text, Map, Newsp ns (up to 10) ize originals) elerators	aper/Magazine)					
Scan to Email (Standard)								
Scan Features	 Auto send to self Email signatures (6 lina options Email signing (requires Scan to Email S/MIME Touchless Workflow Action 	Encryption	email message body (user cont	îgurable), email Embedded We	eb Server confirmation sheet			
Directory Access	Address list via LDAP (Wi	indows Active Directory, Exchar	ige, Notes, Domino), Device Ad	dress Book				
Scan To								
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to USB							
Optional Features	Native Scan to Cloud Re	positories (Dropbox, OneDrive c	Ind Google Drive) ³					
Workflow Scanning (Optior	nal features)							
Scanning Software	Autostore v7 eCopy ScanStation v5.2 ecopy ShareScan v5.2							
Scanning Apps and Xerox App Gallery		e Drive, Microsoft OneDrive, Mi vailable in the Xerox App Galler		Workplace Mobile App (iOS/A	ndroid)			

Colyer.

Security	AltaLink [®] C8130	AltaLink® C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170			
Features	 802.1x Admin Password Reset Audit Log Automatic Software L Email Alerts FIPS 140-2 Hold All Jobs 	g (Monitors and remediates 75	security settings in the follow	ing areas):				
	 McAfee® Embedded Control PII - Login Name PostScript Passwords Remote Services Enablement Remote Start (Mopria(R) or AirPrint[™]) Remote Start (TWAIN) Reprint Saved Jobs Scan to Mailbox (Internal storage) Scheduled Disk with optional hard drive Secure Passcode Length Secure Print Device Policies SIEM SNMP System Timeout USB (Print from USB) USB Port Management USB Port Management 							
	Encrypted and authen Encrypted/Password-P FIPS 140-2 256 bit Ho Immediate Image OW Local Authentication (Network authenticatic Windows server 2012; On-Demand Image O Smart Card authenticat Secure Data Secure Print (up to 10 Expanded Authorisation Authorisation per user SA access based on ne	vhen using Smart Card authen tication to SMTP server for Scc rotected PDF (when using Ema rd Disk Encryption, TLS 1.1/1.2 erwrite/Securely delete jobs us internal database) on to access device and/or devi), NDS, LDAP authentication verwrite (Scheduled, Manual), ition – 144k CAC/PIV Card Sup digit PIN or Network Authentic per service	In to Email il and Network Scan Template /1.3, IPPS, HTTPS, SFTP, SNMI Ing approved algorithms ⁹ ce services via Kerberos (UNIX ncludes sanitation of unused (pport (2048 bit certificate key)	2v3 /Windows Server 2008), SMB (M area of disk ⁹	Vindows Server 2008,			
Xerox [®] Integrated RFID	Full System Common Cr Hide Print Job Names Imaging Security IP Filter, IPsec, IPv6, TLS McAfee® Embedded Co Port disablement includ Security Information an	red to access Print and Print Fe iteria certified by NIAP under H V1.0, V1.2, V1.3, SNMP V1/V2 ntrol (whitelisting), McAfee® Ir ng USB ports d Event Management (SIEM) s	ID Protection Profile for Hardco 2/V3, HTTPs, 802.1X, SFTP itegrity Control (optional) support for McAfee® Enterprise	me restrictions) reflects in the pr opy Devices v1.0 (HCD-PP v1.0) e Security Manager, LogRhythm embedded multifunction printer	and Splunk			
Card Reader (Optional Kit)	the multifunction printer p		an y additional security; WITh	embedded multifunction printer	כמות ופמנפוז ווו			

Fax	AltaLink [®] C8130	AltaLink [®] C8135	AltaLink [®] C8145	AltaLink [®] C8155	AltaLink [®] C8170			
Network Server Fax Feature								
Compatibility ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions								
Maximum Scan Area	A3							
Fax Send Features	Add to Send List (200 nun	- or Two-sided Scanning (up to A3) to Send List (200 numbers maximum) d Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)						
Fax Print Features	One- or Two-sided Printing	g, Staple, Secure Print						
Transmission Resolution	Superfine: 400 x 200 dpi (Fine: 200 x 200 dpi Standard: 200 x 100 dpi							
Internet Fax Features								
Compatibility		ent transmission to remote Inte printout of documents sent vic						
Directory Access	Utilises the Unified Addres	ss Book						
Send/Receive	Send: Multi-page TIFF, PD Receive: TIFF, MTIFF, PDF	F, PDF/A , PDF/A, PS, text, PCL, PRN, JPE	Ĵ					
Resolution	72 x 72 dpi to 600 x 600 d Bit Depth: 1-bit (black-and							
Network Protocols	SMTP (send), POP3 (receiv	ve)						
Compliance	ITU-T T.37							
Walk-up Fax Features (Opti	onal; Customer-Installable	– 1 and 2 lines)						
Compatibility	ITU (CCITT) Group 3							
Speed/Modems	One or Two V.34 modems	: 33,600 bps. Less than 4 secor	nds per page transmission tim	ie				
Compression/Speed	MH/G3, MR/G3, MMR/SG	3, JBIG/SG3						
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super Receive: Accepts all sizes	fine: 600 x 600 dpi						
Fax Send Features	LAN Fax (fax from print dr Auto Fax Transmission Rec Page-by-page Job Status o Delay Start, Build Job, Faw Automatic Memory Resen Automatic Cover Sheets PSTN Fax Batch Send (up to memor Device Address Book (up t Touchless Workflow Acceler	duction at the Machine ourites d y capacity) o 5,000 contacts)						
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password-protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay							
Fax forward	Forward to Email or SMB L Fax Forward on Receive Or							
Fax Reports	Activity, Dial Directory, Gra Report, Broadcast Report	oup Directory, Transmission Co	nfirmation, Pending Fax, Opti	ons Report, On Demand with op	otional hard drive Report, Mailbox			
Directory Access	Utilises the Unified Addres Group fax available	ss Book						
Auto Redial	Up to 14 attempts (per co 1 to 25 minute intervals	ountry requirements)						
Auto Resend	Up to 5 attempts							

Xerox[®] AltaLink[®] C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web	A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher. • Auto-detect Xerox [®] CentreWare [®] Web server and download configurations files for touchless remote installation		
Xerox® Device Manager	 Xerox[®] Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox[®] Device Manager provides: Device monitoring and troubleshooting Remote configuration of SNMP v3 Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities Auto-detect Xerox[®] Device Manager server and download configurations files for touchless remote install 		
Xerox [®] Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server		
Fleet Orchestrator	The Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automaticall set itself on the network and configure		
Novell NDPS/NEPS	Server gateway application: centralised management tool		
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers And Multifunction Printers are available to download. www.xerox.co.uk/en-gb/office/printer-software		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.xerox.co.uk/en-gb/office/printer-software		
Xerox [®] Embedded Web Serv	Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sam- ple set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x to 53.x Opera 25.x to 53.x Chrome 48.x to 72.x		
Support	Install print/scan drivers and online support available via www.support.xerox.com/en-gb		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox [®] Device usage. Eliminates the need for time-con- suming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] Automatic Sup- plies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory		

Xerox[®] AltaLink[®] C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Accounting			
Xerox® Standard Accounting (Standard)			
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts and User Limits via an industry-standard CSV file 		
Accounting Options – Network Accounting (Allows central server to manage all accounting)			
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.co.uk Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at the control panel and pass to a third-party Networking Account Interface with a third-party accounting terminal for accounting user interface 		
Xerox [®] EX-c C8100 Print Ser	ver Powered by Fiery® (Optional)		
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache		
Memory (ESS)	2 GB		
System Disk	500 GB HDD		
Page Description Language	PostScript v 3020		
Features	Access Controls Automatic two-sided printing Booklet Maker – booklet wizard to create booklets Calibration Digitally Signed Software Updates Expert Colour Settings: Profile, Rendering and Simulation Encryption of critical information Fiery API Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery drivers for Mac and Windows Fiery FreeForm Create to create personalised files for free Image Enhance IP filtering Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps and more Job Preview Job Presets N-up PANTONE® Colour Enabled Print from USB flash drive PostScript Security Port Blocking Secure Erase Secure Printing Spool-RIP-Print simultaneously Standard support for long sheet banners User Authentication Watermarks		
Connectivity	10 Base-T/100 Base-TX/1000 Base-T Ethernet		
Optional	Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Colour Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network		

Supplies	Description	Yield		
Toner Cartridge ⁶	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages		
Transfer Belt Cleaner	1 Assembly	160,000 pages		
Second Bias Transfer Roll	1 Assembly	200,000 pages		
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge		
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge		
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge		
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill		
Fan Filter	1 Assembly (AltaLink® C8170)	500,000 pages		
Xerox® Smart Kit®				
Drum Cartridge ⁷	1 Cartridge per Colour	180,000 pages		
Waste Toner Container w/o Suction Filter ⁸	1 Cartridge (AltaLink® C8130/35/45/55)	69,000 pages		
Waste Toner Container with Suction Filter ⁹	1 Cartridge (AltaLink® C8170)	69,000 pages		

Declared in accordance with ISO/IEC 24734.

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis. Not available in all geographical locations.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks. Sold separately in some geographical locations.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area

coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points. Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 35% colour/65% black-and-white pages.

⁸ Waste Toner Container yield will vary depending on type of image, area coverage % and job run length.
⁹ With optional hard drive.

© 2021 Xerox Corporation. All rights reserved. Xerox®, AltaLink®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare® and Global Print Driver® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered US marks. Mopria is a trademark of the Mopria Alliance®. The information in this brochure is subject to change without notice. 08/21 TSK-2207 BR29564 AC8SS-03EE

For more information, contact your Xerox Authorised Channel Partner...



