

# Revorla Press EC1100

## Specifications

### Basic Specifications / Print Function

Item	Description	
Type	Console	
Colour Capability	Full Colour	
Printing Resolution	2,400 x 2,400 dpi	
Continuous Print Speed <sup>*1</sup>	A4	100 ppm
	A3	52 ppm
Paper Size <sup>*2</sup>	Tray 1, 2, 3	Standard size: Max A3, 11 x 17", Min A5 Custom size: 140 x 182 mm to 330 x 488 mm
	Bypass Tray (Tray 5) <sup>*3</sup>	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 660 mm
Paper Weight	Tray 1, 2, 3	64 to 256 gsm
	Bypass Tray (Tray 5) <sup>*3</sup>	52 to 350 gsm <sup>*4</sup>
Paper Tray Capacity <sup>*5</sup>	Standard	570 sheets x 3-tray
	Max	10,760 sheets (Standard + Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DS-L)
Paper Tray Capacity <sup>*5</sup> Optional	High Capacity Feeder C3-DS + Multi Sheet Inserter for Banner Print	2,100 sheets x 2-tray + 250 sheets
	2nd High Capacity Feeder C1-DS + High Capacity Feeder C3-DS+ Multi Sheet Inserter for Banner Print	2,100 sheets x 2-tray x 2-connection + 250 sheets
	Air Suction Feeder C1-DS <sup>*6</sup>	2,200 sheets x 2-tray + 250 sheets
	Air Suction Feeder C1-DSXL <sup>*6</sup> + Banner Unit for Air Suction Feeder C1-DSXL	900 sheets <sup>*7</sup> + 2,200 sheets + 250 sheets
	Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DS-L <sup>*6</sup>	2,200 sheets x 2-tray x 2-connection + 250 sheets
	Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DSXL-L <sup>*6</sup> + Banner Unit for Air Suction Feeder C1-DSXL	2,200 sheets x 2-tray + 900 sheets <sup>*7</sup> + 2,100 sheets + 250 sheets
Output Tray Capacity <sup>*5*8</sup>	500 sheets(A3)	
Power Supply	AC200-240 V +/- 10 %, 24 A, 50/60 Hz	
Maximum Power Consumption	5.76 kW	
Dimensions <sup>*9</sup>	W 2,671 x D 834 x H 1,370 mm	
Weight <sup>*9</sup>	727 kg	

Note: Multi Sheet Inserter for Banner Print cannot be directly connected to the main unit. It is used by connecting to High Capacity Feeder C3-DS.

\*1: When continuously printing a single document. 52 to 300 gsm, uncoated paper. Print speed may be reduced depending on conditions of output data, on whether auto image quality adjustment is performed, on whether the job includes a mixture of paper sizes and types, and other reasons.

\*2: Image loss width: Lead edge 4.0 mm, Trail edge 2.0 mm, Front 2.0 mm, Rear 2.0 mm.

\*3: Bypass Tray is Multi Sheet Inserter for Banner Print.

\*4: Banner Printing 52 to 220 gsm.

\*5: 82 gsm paper.

\*6: Multi Sheet Inserter for Banner Print is included.

\*7: 100 sheets for paper longer than 864 mm (90 gsm).

\*8: Offset Catch Tray.

\*9: Includes main unit and High Capacity Feeder C3-DS. Excludes output tray and external print server.

## High Capacity Feeder C3-DS (Optional)

Item	Description	
Paper Size*1	High Capacity Feeder	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 488 mm
	Bypass Tray (Optional)	Standard size: Max A3, 11 x 17", Min A6 Custom size: 100 x 148 mm to 330 x 660 mm
Paper Weight	High Capacity Feeder	52 to 350 gsm
	Bypass Tray (Optional)	52 to 350 gsm*2
Feeding Capacity / Number of Tray*3	High Capacity Feeder	2,100 sheets x 2-tray
	Bypass Tray (Optional)	250 sheets
Power Supply	AC100-120 V +/- 10 %, 6 A, AC220 - 240 V +/- 10 %, 4 A, 50/60 Hz	
Maximum Power Consumption	880 W	
Dimensions	W 988 x D 762 x H 992 mm	
Weight*4	232 kg	

Note: Optional Multi Sheet Inserter for Banner Print is required. Note: When High Capacity Feeder C3-DS is connected to 2nd High Capacity Feeder C1-DS, the optional Multi Sheet Inserter for Banner Print attached to the left module.

\*1: When setting main scanning 98 to 182 mm paper, Post Card Kit 2 is required.

\*2: 82 to 220 gsm for paper longer than 488 mm.

\*3: 82 gsm paper.

\*4: Including Multi Sheet Inserter for Banner Print.

## Air Suction Feeder C1-DS / C1-DSXL (Optional)

Item	Description		
		Air Suction Feeder C1-DS	Air Suction Feeder C1-DSXL + Banner Unit for Air Suction Feeder C1-DSXL
Paper Size*1	High Capacity Feeder	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 488 mm	Standard size: Max A3, 11 x 17", Min A6 Custom size: 210 x 210 mm to 330 x 1,200 mm*2 (Upper tray) 98 x 148 mm to 330 x 488 mm (Lower tray)
	Bypass Tray	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 146 mm to 330 x 660 mm	
Paper Weight	High Capacity Feeder	52 to 400 gsm	52 to 400 gsm*3
	Bypass Tray	52 to 350 gsm*4	
Feeding Capacity / Number of Tray*5	High Capacity Feeder	2,200 sheets x 2-tray	900 sheets*6 + 2,200 sheets
	Bypass Tray	250 sheets	
Power Supply	AC100-120 V +/- 10 %, 6 A, AC220-240 V +/- 10 %, 4 A, 50/60 Hz		
Maximum Power Consumption	880 W		
Dimensions	W 988 x D 762 x H 992 mm	W 1,580 x D 762 x H 992 mm	
Weight*7	194 kg	213 kg	

Note: Multi Sheet Inserter for Banner Print is included. Note: Air Suction Feeder C1-DSXL can feed long paper only from the Upper tray.

\*1: When setting main scanning 98 to 182 mm paper, Post Card Kit for Air Suction Feeder is required.

\*2: Duplex Automatic Print supports paper size up to 330 x 864 mm.

\*3: For long paper from 330 x 488 mm to 330 x 660 mm: 52 to 350 gsm; for paper up to 330 x 864 mm: 52 to 300 gsm; for paper up to 330 x 1,200 mm: 52 to 256 gsm. Duplex Automatic Print supports paper weight up to 300 gsm.

\*4: 52 to 220 gsm for paper longer than 488 mm.

\*5: 82 gsm paper.

\*6: 100 sheets for paper longer than 864 mm (90 gsm).

\*7: Including Multi Sheet Inserter for Banner Print.

## Finisher D6 / Finisher D6 with Booklet Maker (Optional)

Item	Description	
	Finisher D6	Finisher D6 with Booklet Maker
Type	Output Tray	Sort / Stack
	Finishing Tray	Sort (Offset available) / Stack (Offset available)
	Booklet Tray	- / Sort / Stack
Paper Size	Output Tray	Standard size: Max A3, 11×17", Min A6 Custom size: 98 x 148 mm to 330 x 1,200 mm <sup>1</sup>
	Finishing Tray	Standard size: Max A3, 11×17", Min A5 Custom size: 148 x 148 mm to 330 x 488 mm
Paper Weight	Output Tray	52 to 400 gsm
	Finishing Tray	52 to 350 gsm
Paper Capacity <sup>2</sup>	Output Tray <sup>1</sup>	500 sheets (A4)
	Finishing Tray Without Stapling	A4: 3,000 sheets JIS B4 or larger: 1,500 sheets Mixed Size Stacking <sup>3</sup> : 350 sheets
	Finishing Tray With Stapling	A4: 200 sets or 3,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets
	Booklet Tray	- / 20 sets <sup>4</sup>
Staple	Capacity	100 sheets (90 gsm or less) <sup>5</sup>
	Paper Size <sup>6</sup>	Standard size: Max A3, 11 x 17", Min JIS B5 Custom size: 182 x 182 mm to 297 x 432 mm
	Paper Weight	52 to 350 gsm
	Position	Single stapling, Dual stapling, 4 stapling
Punch <sup>7</sup>	Number of Holes	2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications)
	Paper Size <sup>8</sup>	Standard size: Max A3, 11 x 17", Min JIS B5 (2-hole punch, 3-hole punch), A4 (4-hole punch) Custom size: 203 x 182 mm to 297 x 431 mm
	Paper Weight	52 to 220 gsm
Booklet Finishing	Capacity <sup>9</sup>	- / Saddle Staple: 30 sheets (90 gsm or less) Single Fold: 5 sheets (220 gsm or less)
	Paper Size	- / Standard size: Max A3, 11×17", Min JIS B5 Custom size: 182 x 257 mm to 330 x 488 mm
	Paper Weight	- / 60 to 350 gsm
Power Supply	AC100-240 V +/- 10 %, 3 A (100 V) / 1.5 A (240 V), 50/60 Hz	
Maximum Power Consumption	360 W	
Dimensions	W 855 x D 725 x H 1,204 mm When Folder Unit CD2 is installed: W 1,092 x D 725 x H 1,204 mm	W 892 x D 725 x H 1,204 mm When Folder Unit CD2 is installed: W 1,129 x D 725 x H 1,204 mm
Weight	87 kg When Folder Unit CD2 is installed: 142 kg	107 kg When Folder Unit CD2 is installed: 162 kg

Note: Interface Decurler Module D1 is required.

\*1: For paper longer than 330 x 488 mm, the capacity is not guaranteed. When the optional Banner Print Extension Kit is installed, 150 sheets of long paper up to 330 x 660 mm; 100 sheets of long paper up to 330 x 864 mm; 10 sheets of long paper up to 330 x 1,200 mm can be stacked.

\*2: 82 gsm paper.

\*3: When larger size sheets are stacked on top of smaller size sheets.

\*4: When 16 sheets/set.

\*5: 65 sheets for sizes exceeding A4.

\*6: Available staple positions vary depending on the paper size.

\*7: Optional.

\*8: Available number of punch holes varies depending on the paper size.

\*9: The maximum number of sheets varies depending on the paper weight. Booklet may not be tightly closed depending on the size or type of the paper.

## Offset Catch Tray / Long Catch Tray (Optional)

Item	Description	
	Offset Catch Tray	Long Catch Tray
Paper Size	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 660 mm*1	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 1,200 mm*2
Paper Weight	52 to 400 gsm	
Paper Capacity <sup>3</sup>	500 sheets	300 sheets (Paper length up to 488 mm) 100 sheets (Paper length above 488 to 864 mm) 10 sheets (Paper length above 864 to 1,200 mm)
Dimensions	W 406 x D 393 x H 184 mm	W 512 x D 396 x H 308 mm*4
Weight	6 kg	4 kg*5

\*1: Paper capacity is guaranteed up to 488 mm.

\*2: When Long Paper Extension Kit is not installed, the capacity is guaranteed up to 660 mm.

\*3: 90 gsm paper.

\*4: When Long Paper Extension Kit is installed, W 941 x D 396 x H 495 mm.

\*5: When Long Paper Extension Kit is installed, 5 kg.

## Folder Unit CD2 (Optional)

Item	Description	
Z Fold Half Sheet	Paper Size	A3, 11 x 17", JIS B4
	Paper Weight	60 to 90 gsm
Tri-fold	Paper Size	A4, Letter
	Paper Weight	60 to 90 gsm
	Paper Capacity*	30 sheets
Power Supply	AC100-240 V +/- 10 %, 1 A (100 V) / 0.5 A (240 V), 50/60 Hz	
Maximum Power Consumption	120 W	
Dimensions	W 232 x D 725 x H 992 mm	
Weight	55 kg	

Note: Finisher D6, or Finisher D6 with Booklet Maker is required.

Note: Power supply separate from the Main Unit is required.

\*: 82 gsm paper.

## Insertter D1 (Optional)

Item	Description
Paper Size	Standard size: Max A3, 11 x 17", Min A5 Custom size: 182 x 148 mm to 330 x 488 mm
Paper Weight	52 to 350 gsm
Paper Capacity <sup>1</sup>	250 sheets
Power Supply	Supplied from Interface Decurler Module D1
Dimensions	W 700*2 x D 725 x H 1,235 mm
Weight	45 kg

Note: Finisher D6, Finisher D6 with Booklet Maker or High Capacity Stacker A1 is required.

\*1: 82 gsm paper.

\*2: The width of the paper transfer part only when connected to the device is 165 mm.

## Interface Decurler Module D1 (Optional)

Item	Description
Power Supply	AC100-240 V +/- 10 %, 2.5 A (100 V) / 1 A (240 V), 50/60 Hz
Maximum Power Consumption	250 W
Dimensions	W 340 x D 725 x H 992 mm
Weight	40 kg

Note: Interface Decurler Module D1 is necessary for connecting Finisher D6, Finisher D6 with Booklet Maker or High Capacity Stacker A1 to the printer.

## Square Back Fold Trimmer D1 (Optional)

Item	Description	
Paper Size	Same as the paper size of the Finisher D6 Booklet Finishing.	
Paper Weight	Same as the paper weight of the Finisher D6 Booklet Finishing.	
Booklet Tray Capacity <sup>*1</sup>	20 sets (15 sheets bind and below), 15 sets (16 sheets bind and above)	
Face Trim	Capacity <sup>*2</sup>	Saddle Staple: 30 sheets, Single Fold: 5 sheets
	Trim dimensions	2 to 20 mm
Square Back Capacity <sup>*2*3</sup>	30 sheets	
Power Supply	AC100-240 V +/- 10 %, 1.0 A (100 V) / 0.6 A (240 V), 50/60 Hz	
Maximum Power Consumption	144 W	
Dimensions	W 1,066 x D 725 x H 552 mm	
Weight	100 kg	

Note: Finisher D6 with Booklet Maker is required.

\*1: Paper may not be accepted depending on paper type and other usage conditions.

\*2: The capacity can decrease depending on type and weight of paper being used and other conditions.

\*3: Square back finishing is not supported for single-folding and saddle stapling of less than 5 sheets.

## Crease / Two-sided Trimmer D2 (Optional)

Item	Description	
Two-sided Trim	Paper Size	Standard size: Max A3, 11 x 17", Min A4, Letter Custom size: 194 x 210 mm to 330 x 488 mm
	Paper Weight	52 to 350 gsm
	Trim dimensions	One side: 6 to 25 mm
Crease	Paper Size	Standard size: Max A3, 11 x 17", Min JIS B5 Custom size: 182 x 210 mm to 330 x 488 mm
	Paper Weight <sup>*1</sup>	52 to 350 gsm
	Number of lines <sup>*2</sup>	1 to 5
Power Supply	AC100-240 V +/- 10 %, 4 A (100 V) / 2 A (240 V), 50/60 Hz	
Maximum Power Consumption	480 W	
Dimensions	W 605 x D 725 x H 992 mm	
Weight	128 kg	

Note: Finisher D6, or Finisher D6 with Booklet Maker is required.

\*1: When using the booklet finishing. 157 gsm or more is supported for single sheet.

\*2: The continuous print speed will decrease significantly as the number of lines increases.

## High Capacity Stacker A1 (Optional)

Item		Description
Paper Capacity*1	Output Tray*2	500 sheets*3
	High Capacity Stacker – Stacker Cart	5,000 sheets
Paper Size	Output Tray	Standard size: Max A3, 11 x 17", Min A6 Custom size: 98 x 148 mm to 330 x 1,200 mm
	High Capacity Stacker – Stacker Cart	Standard size: Max A3, 11 x 17", Min JIS B5 Custom size: 203 x 182 mm to 330 x 488 mm
Paper Weight	Output Tray	52 to 400 gsm
	High Capacity Stacker – Stacker Cart	52 to 300 gsm
Power Supply		AC100-240 V +/- 10 %, 1.5 A (100 V) / 0.8 A (240 V), 50/60 Hz
Maximum Power Consumption		192 W
Dimensions		W 800 x D 725 x H 1,042 mm
Weight*4		155 kg

Note: Interface Decurler Module D1 is required.

\*1: 80 gsm paper.

\*2: For paper longer than 330 x 488 mm, the capacity is not guaranteed. When the optional Banner Print Extension Kit is installed, 100 sheets of long paper up to 330 x 864 mm; 10 sheets of long paper up to 330 x 1,200 mm can be stacked.

\*3: When the optional Banner Print Extension Kit is installed, 250 sheets.

\*4: Including Stacker Cart.

Please contact your local Fujifilm partner or visit:  
[print-emea.fujifilm.com/product/revoria-press-ec1100/](http://print-emea.fujifilm.com/product/revoria-press-ec1100/)

# Colyer.

hello@colyer.co.uk  
 LONDON: 020 7833 0888  
 UK: 01483 596200  
[colyer.co.uk](http://colyer.co.uk)



Fujifilm Print



Fujifilm Print



@FujifilmPrint