

Datasheet



HP DesignJet T850 36-in Multifunction **Printer**

The world's easiest A3-A1 printing experience to maximize your team's agility¹



THE EASIEST¹—Multi-size printing in one click

- Do it all—also print A3 jobs using the integrated input tray, without manually changing from roll
- Achieve high-quality CAD and renders across print sizes with HP Flex Tech Inks.
- Avoid distractions with fewer ink interventions thanks to 130/300-ml cartridges.
- Simplify scan and copy workflows with personalized one-click shortcuts from the front panel.

CONNECTED—Secure and seamless collaboration

- Save time with HP Click—print in fewer steps and avoid reprinting with print preview.
- Protect your printer and data from cyberthreats without any effort thanks to HP Wolf Pro
- Stay on task with HP App²—manage your device and print from virtually anywhere using your mobile or tablet.
- Share drawings and collaborate with colleagues wherever they are with the easy-to-use frontloading scanner.

GO BEYOND-Meet office and environmental needs

- Advance environmental goals—printer is made with at least 40% recycled plastics³ and recyclable supplies⁴.
- Invest in a robust and compact plotter that's designed to last.
- Reduce energy and ink waste—auto schedule printer on/off usage and enjoy efficient ink maintenance routines.

For more information, please visit https://www.hp.com/go/designjet-t850-mfp

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Based on test results using HP Click with the HP DesignJet T850. This solution enables printing in fewer steps compared to main competitor printing solutions. Printing a 5-page mixed job set with A1 and A3 takes 3 steps using HP Click vs. 12 steps with competitor A and 8 steps with competitor B. Testing performed by Sogeti, April 2023. Detailed test report is available upon request.

² Requires HP App download available at https://www.hp.com/go/mobileprinting. Certain features are available in English language only and may vary by printer model/country, and between desktop/mobile applications. HP reserves the right to introduce charges for use of functionality facilitated by the HP App. Internet access required and may not be available in all countries. HP account required for full functionality. List of supported

operating systems available in app stores.

3 Declared %RCP content is based on the quantity and weight of parts made with RCP resin over the total plastic parts.

⁴ Program availability varies. See https://www.hp.com/go/recycle

Technical specifications

Ink drop 6 p1 (C, M, Y); 12.6 p1 (mK) Printheads 1 (C, M, Y, mk) Printhead nozzles 1376 per color; 5504 in total Line accuracy ±0.1%² Max optical density 15 L* min/1.7 D³ Multifunction capabilities Scan speed Up to 3.81 cm/sec (color, 200 dpi) Up to 11.43 cm/sec (grayscale, 200 dpi) Up to 11.43 cm/sec (grayscale, 200 dpi) Technology Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method Scan format JPEG, PDF, TIFF Scan destinations Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Handling Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray; 210 x 279 to 305 x 457 mm Manual feed; 210 x 279 to 305 x 457 mm Manual feed; 210 x 279 to 914 x 1676 mm Standard sheets Input tray; 210 x 279 to 914 x 1676 mm Standard sheets Up to 0.3 mm Applications Line drawings; Renderings; Presentations; Maps; Posters Hendridsk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11 bi/g/n Native print languages TiFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and IOS devices, Windows and macOS printer drivers Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows	Print	
Technology March Set 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Sete 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 x 5 mm Set 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5	Print speed	25 sec/page on A1, 90 A1 prints per hour ¹
Regins Select 5 x 5 x 5 x 5 mm Select 5 x 5 x 5 x 5 x 5 x 5 mm Select 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5	Print resolution	Up to 2400 x 1200 optimized dpi
Sheet Sis Sis Sis Sis Sis Sis Sis Sis Minimarks (T. M. Y. P. 12.5 p.) First Ord Sis Sis Sis Sis Minimarks (T. M. Y. P. 12.5 p.) First Ord Sis Sis Sis Sis Minimarks (T. M. Y. P. 12.5 p.) First Ord Sis Sis Sis Sis Minimarks (T. M. Y. P. 12.5 p.) First Ord Sis	Technology	HP Thermal Inkjet
Printends of policin, M. Yer, 12.6 pt (mst) Printends of 10, M. Yer and 11, 12.6 pt (mst) Printends of 12.6 M. Yer and 11, 12.6 pt (mst) Printends of 1375 per color; 5504 at total Line accuracy 10.197 Moliforction coadilities Soan speed Up to 1811 mol/17 DP Moliforction coadilities Soan speed Up to 1811 mol/17 DP Moliforction coadilities Soan speed Up to 1812 mol/17 DP Soan resolution Up to 6000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 11.43 cm/sec (gayscale, 200 dpt) Up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 11.43 cm/sec (gayscale, 200 dpt) Up to 10.000 up to 10.	Margins	
Prothesian Duziles 1 KL, N. Y. CHIO 13 To per color; 5504 in total 14 To accuracy 2 CHIP Minimum line width 0 CM minimum line width 15 L* min/17 CP Minimum line width 15 L* minimum line 15 Can desiration 15 Sean desirat	Ink types	Pigment-based (C, M, Y, mK)
Printhead nozales 1376 per color; \$504 in total Line accuracy 51 MP Minimum line widt 50 0.02 mm Noi reader drived Max optical density 151 min/1.7 D1 Multifunction capabilities Soan speed Up to 3.81 cm/sec (color; 200 dp) Up to 1.143 cm/sec (color; 200 dp) Up to 1.143 cm/sec (color; 200 dp) Up to 500 dp; Soan resolution Up to 600 dp; Technology Sheeffed, GS (Contact Image Sensor), media jum detection sensor, front feed scanning method Soan format JPEG, POI, TFF Thickness Up to 0.8 mm Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal Media Finding Sheef feed, roll feed, input tray (50 sheet capacity), roll feed Media Medi	Ink drop	6 pl (C, M, Y); 12.6 pl (mK)
Line accuracy 4.0.1%2 Milkimum tries width 0.0.2 mm (via raster driver) Milkimum tries width 1.0.2 mm (via raster driver) Up to 0.3.81 cm/sec (paysocial, 200 dp) Up to 1.3.81 cm/sec (paysocial, 200 dp) Up to 0.3.81 cm/sec (paysocial, 200 dp) Scan format Jess, P.PE, IFF Scan destinations Scan to meat Jess, P.PE, IFF Scan destinations Scan to emal. and work, and USB. Scan to cloud, computer, and mobile through HP Smart app. Tickness Up to 0.3 mm Media Inauding Sheet feed, roll feed, input tray (SO sheet capacity), media bis, automatic horizontal cutter Tool size 305 to 914 mm Maximum oil dismeter Input tray, Cal 7.0.3 mm Maximum oil feed; Input tray Inclusions Up to 0.3 mm Maximum oil feed; Input tray Inclusions Up to 0.3 mm Maximum oil feed; Input tray Inclusions Up to 0.3 mm Maximum oil feed; Input tray, Up	Printheads	1 (C, M, Y, mK)
New politic diversity 15 tr mini 7.7 p.* 1 Make optical devisity 15 tr mini 7.7 p.* 1 Make optical devisity 15 tr mini 7.7 p.* 1 Make optical devisity 15 tr mini 7.7 p.* 1 Make optical devisity 15 tr mini 7.7 p.* 1 Make optical devisity 15 tr mini 7.7 p.* 1 Up to 13.43 croylex (sole, 200 dp) Up to 1500 db Up to 13.43 croylex (sole, 200 dp) Up to 1500 db Up to 15.43 croylex (sole, 200 dp) Scan resolution Up to 600 db U	Printhead nozzles	1376 per color; 5504 in total
Multifuction capabilities Scan speed Up to 3.81 cm/sec feeler, 200 dpil Up to 1.43 cm/sec feeler, 200 dpil Up to 5.60 dpil Technology Sheetfed, CIS (Ecritact Image Sersor), media jam detection sensor, front feed scarring method Scan format JPEG, PDF, TBF Scan destinations Scan to sema, network, and USB. Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Hendring Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll size 365 to 914 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 305 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 305 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 316 x 1676 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 mm Stendard Sheets Input tray 210 x 278 to 306 x 457 mm Maximum roll Glameter 100 roll mm Maximum roll Glameter 100 to 200 gm/r (roll of 100 roll mm Maximum roll Glameter 100 roll mm Maximum roll	Line accuracy	±0.1% ²
Scan pased Up to 3.81 cm/sec (polyscole, 200 dpl) Up to 11.43 cm/sec (polyscole, 200 dpl) Scan resolution Up to 600 dpl Up to 11.43 cm/sec (polyscole, 200 dpl) Scan resolution Up to 600 dpl Up to 11.43 cm/sec (polyscole, 200 dpl) Scan resolution Up to 600 dpl Up to 11.43 cm/sec (polyscole, 200 dpl) Scan to comain, network, and USB. Scan to cloud, computer, and mobile through NP Smart app. Up to 8 mm Medical Up to 8 mm Up to 9 m	Minimum line width	0.02 mm (via raster driver)
Scan speed Up to 3.81 cm/sec (color, 200 dp) Up to 6.00 dp) Scant resolution Up to 6.00 dp) Technology Sheetfed, Cis Contact Image Sensor), media jam detection sensor, front feed scanning method Scant format JPES, PDE, TBF Scant destreations San to email, network, and USB. Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Harding Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll size 36 sto 914 mm Maximum roll diameter 100 mm Sheet size lipput tray, 210 x 279 to 305 x 457 mm Manual feed 210 x 279 to 305 x 457 mm Manual feed 210 x 279 to 314 x 1676 mm Standard sheets lipput tray, 24 x 279 to 314 x 1676 mm Standard sheets lipput tray, 24 x 279 to 314 x 1676 mm Standard sheets lipput tray, 24 x 279 to 315 x 457 mm Manual feed 210 x 279 to 315 x 457 mm Manual feed 210 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 315 x 457 mm Manual feed 210 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 315 x 457 mm Manual feed 210 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 315 x 457 mm Manual feed 210 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 514 x 1676 mm Manual feed 210 x 279 to 514 x 1676 mm Standard sheets lipput tray, 24 x 279 to 514 x 1676 mm Manual feed 210 x 279 to 514 x 1676 mm Manual feed 31 x 279 to 514 x 1676 mm Manual feed 31 x 279 to 514 x 1676 mm Manual feed 31 x 279 to 514 x 170	Max optical density	15 L* min/1.7 D ³
Up to 11.43 cm/sec (gayscale, 200 dp) Scan resolution Up to 600 dpi Technology Sheeffed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method Scan format JPES, DOR, TIFF Scan destinations Scan to email, network, and USB, Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Handling Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll Sze 360 to 91.4 mm Maximum roll diameter 10.0 mm Maximum roll diamete	Multifunction capabilities	
Scan resolution Up to 600 dpi Technology Sheeffed, Cis (Contact Image Sensor), media jam detection sensor, front feed scanning method Scan format JPES, DPS, DFIFF Scan destinations Scan to email, network, and USB, Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Handling Sheef feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray, 210 x 279 to 305 x 457 mm Manual feed; 210 x	Scan speed	
Scan format JPEG, PDF, TFF Scan destination Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Handling Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter 808 laze 369 to 914 mm Marsual feed 2 10 x 279 to 305 x 457 mm Mansual feed 2 10 x 279 to 305 x 457 mm Mansual feed 2 10 x 279 to 316 x 1876 mm Standard sheets Input tray, 24, A3, A2, A1, A0 Grammage 60 to 280 gm/ frout/mansual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations, Maps, Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi 802.11b/g/n Native print languages TFF, JPEG, URF, PDF, HP-CL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, rendete printing, Apple Ar/Print and HP Smart app for Android and IOS devices, Windows and macOS printer drivers, printing support for Chromed Sy print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features 1407 x 701 x 967 mm Shopping 1575 x 570 x 650 mm Weight Printer 60 kg Mhart's in the box HP Designale TSSO MFP, printheads, inic cartridges, printer stand, spindle, guide, poster, warrouty flyer, power cord HP Sottware and solutions Remove print enabled Ves One-click multi-size printing 40 HP Designale TSSO MFP, printheads, inic cartridges, printer stand, spindle, guide, poster, warrouty flyer, power cord HP Sottware and solutions Permote print enabled Ves One-click multi-size printing 42 B/W (operating), -16 dB(A) (Idle) Sound power 42 B/B/I (operating), -16 dB(A) (Idle) Sound power 42 B/B/I (operating), -16 dB(A) (Idle) Sound power 53 W (printing), -11 W (ready), -3.5 W (Selepi), -0.1 W (standby), Auto-scheduled printer on loff usage.	Scan resolution	
Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP Smart app. Thickness Up to 0.8 mm Media Handling Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Roll size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray: 210 x 279 to 30 x 457 mm Manual feed 210 x 279 to 30 x 457 mm Manual feed 210 x 279 to 30 x 457 mm Manual feed 24 A, A3, A2, A1, A0 Grammage 60 to 280 g/m² (input tray) Applications Line drawings, Renderings; Presentations; Maps; Posters Memory 2 GB Hand disk None ConnectMity Interfaces Gigabit Ethernet (10006ase-1), Wi-Fi 802.1 b/g/n Native print languages TIFE, JPEC, URF, DPE, HP-GL/Z, HP-RTL, CALS G4 Printing paths Wi-Fi Diver, temote printing, Apple Arbrint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Winding, Feed, Calz or they mildows HP Security Returns HP Security Meanager, SEM Integration Direntsions (W.x. D.x.) Printer 1407 x 701 x 967 mm Marginet 1407 x 701 x 967 mm Medight Printing 33.5 kg What's in the box HP Design, let T850 MPP printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and Southors Provers Provers Consumption 37% Operating turned 42 dis(A) (operating), <16 dB(A) (diel) Operating plumidity 20 to 80% RH Operating turned 140 x 20 to 80% RH Operating temperature 42 dB(A) (operating), <16 dB(A) (diel) Operating stitute Consumption 35 W (printing), <11 W (ready), <3.5 W (steepl, <0.1 W (standby), Auto-scheduled printer onloff usage.	Technology	Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method
Media Handling Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter Solisize 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray, 210 x 279 to 305 x 457 mm Manual feed, 210 x 279 to 301 x 1676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Standard sheets Input tray, 240 x 279 to 301 x 4676 mm Grammage 60 to 280 gtm² (roll/manual feed); 60 to 220 gfm² (roput tray) Thickness Up to 0.3 mm Applications Line drawings. Renderings; Presentations; Maps; Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabli Ethernet (10008ase-1), Wi-Fi 802.11b/g/n Native print languages TiFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Prenting paths Wi-Fi Direct, remote printing, Apple Alephir and HP Smart app for Android and IOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Directs Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure both, withinking, Security event logging, Disable network ports and protocols, SNMPv3, 802.1 x compatibility, TLS/SSL, NTLM v2, HP Web letAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight What's inte book HP Designlet TBSO MP, printheads, ink cartridges, printer stand, spindle, guide, poster, werranty flyer, power cord HP Software and solution Printer 1407 x 701 x 967 mm Shipping 83.5 kg What's inte book HP Designlet TBSO MP, printheads, ink cartridges, printer stand, spindle, guide, poster, werranty flyer, power cord HP Software and solution Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight What's inte box HP Designlet TBSO MP, printheads, ink cartridges, printer stand, spindle,	Scan format	JPEG, PDF, TIFF
Hendling Sheet Feed, roll Feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter	Scan destinations	Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP Smart app.
Handling Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter 80l size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray: 210 x 279 to 30 x 457 mm	Thickness	Up to 0.8 mm
Roll size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray, 210 v, 279 to 305 v, 457 mm Manual feed; 210 v, 279 to 914 v, 1676 mm Standard sheets Input tray, 24, A3 Manual feed; 210 v, 279 to 914 v, 1676 mm Standard sheets Input tray, 24, A3 Manual feed; A4, A3, A2, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations; Maps; Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi B02.11 b/g/n Native print languages TIFF, IPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Alprint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Normore OS, print Horn USB per drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network; ports and protocols, SNMPv3, 802.1x compatibility, TLS/SS, INTM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 8.3 kg One-Click multi-size printing Pees Powton HP Designate 1850 MFR, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-Click multi-size printing Pees Powton HP Score Standard (Gele) Operating altitude Up to 3000 m Storage temperature - 25 to 55°C Acoustics Cound power 5.8 B(A) (operating), <1.4 B(A) (die) Power Consumption 35 W (grinting), <11 W (seady), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer onloff usage.	Media	
Roll size 369 to 914 mm Maximum roll diameter 100 mm Sheet size Input tray, 210 v, 279 to 305 v, 457 mm Manual feed; 210 v, 279 to 914 v, 1676 mm Standard sheets Input tray, 24, A3 Manual feed; 210 v, 279 to 914 v, 1676 mm Standard sheets Input tray, 24, A3 Manual feed; A4, A3, A2, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations; Maps; Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi B02.11 b/g/n Native print languages TIFF, IPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Alprint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Normore OS, print Horn USB per drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network; ports and protocols, SNMPv3, 802.1x compatibility, TLS/SS, INTM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 8.3 kg One-Click multi-size printing Pees Powton HP Designate 1850 MFR, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-Click multi-size printing Pees Powton HP Score Standard (Gele) Operating altitude Up to 3000 m Storage temperature - 25 to 55°C Acoustics Cound power 5.8 B(A) (operating), <1.4 B(A) (die) Power Consumption 35 W (grinting), <11 W (seady), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer onloff usage.	Handling	Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter
Sheet size Input tray, 210 x 279 to 305 x 457 mm Manual Idead; 210 x 279 to 314 x 1676 mm Standard sheets Input tray, 210 x 279 to 314 x 1676 mm Standard sheets Input tray, 24, A3 Manual Idead; 210 x 279 to 314 x 1676 mm Grammage 60 to 280 glm² (roll/manual feed); 60 to 220 glm² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations; Maps; Posters Memory 2 GB Memory 2 GB Memory 2 GB Mone Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print lanquages TFF, JPEG, URF, DPG, HP-GL/Z, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Air/Print and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome GS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/Z driver for Windows Security features HP Secure Boot, whiteliating, Security even Logism, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Weight Printer 60 kg Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Cone-click multi-size printing Profit of HP Designet 1850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions Remote print enabled Ves Cone-click multi-size printing Yes Cone-click multi-size printing Profit of printer 37% Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound provers -4 2 dB(A) (operating), <16 dB(A) (diel) Power Consumption 35 W (printing), <11 W (seady), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Roll size	369 to 914 mm
Manual feed, 210 x 279 to 914 x 1676 mm	Maximum roll diameter	100 mm
Manual feed: AA, A3, A2, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 3, mm Applications Line drawings; Renderings; Presentations; Maps; Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi 802.11b/g/n Native print languages TiFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer drives; printing support for Chrome Os, print from USB per drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimersions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP Designaler T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solution HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Ves One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Operating humiti-size printing Ves Environmental ranges Recycled plastic in printer 25 to 40°C Operating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Querating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Querating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Querating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Querating humiti-size printing Ves Environmental ranges Recycled plastic in printer 376 Querating humiti-size printing Ve	Sheet size	Input tray: 210 x 279 to 305 x 457 mm Manual feed: 210 x 279 to 914 x 1676 mm
Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations; Maps; Posters 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages TiFF, JPEG, URE, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg What's in the box HP Designate T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Environmental ranges Environmental ranges Security feature Stone Good on Storage temperature 5 to 40°C Operating humidity 20 to 80% RH Operating humidity 20 to 80% RH Operating semperature 5 to 40°C Operating semperature 4 2 dB(A) (operating), <14 dB(A) (idle) Sound prossure 4 2 dB(A) (operating), <16 dB(A) (idle) Sound prossure 4 2 dB(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Standard sheets	
Applications Line drawings; Renderings; Presentations; Maps; Posters Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages TFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Air/Print and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, PF-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JerAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP Designalet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Ves One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating emperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature 5 to 40°C Operating slitude Up to 3000 m Storage temperature 42 d B(A) (operating), <16 dB(A) (dile) Sound prossure 42 d B(A) (operating), <3.4 B(A) (dile) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Grammage	60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray)
Memory 2 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi B02.11b/g/n Native print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPinit and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM integration Dimensions (Wx D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Recycled plastic in printer 5 to 40°C Operating temperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound prower 5.8 B(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Thickness	Up to 0.3 mm
Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages TIFF, JPEG, URF, PDF, HP-GL/Z, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Air Print and HP Smart app for Android and IOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/Z driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating latitude Up to 3000 m Storage temperature - 25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 58 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Applications	Line drawings; Renderings; Presentations; Maps; Posters
Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi B02.11b/g/n Native print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v.2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating lumidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Memory	2 GB
Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple Air/Print and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature -25 to 85°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Hard disk	None
Native print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature 42 dB(A) (operating), < 16 dB(A) (idle) Sound power 5 kB (A) (operating), < 3.4 B(A) (idle) Power Consumption 35 W (printing), < 11 W (ready), < 3.5 W (sleep), < 0.1 W (standby), Auto-scheduled printer on/off usage.	Connectivity	
Native print languages TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4 Printing paths Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature 42 dB(A) (operating), < 16 dB(A) (idle) Sound power 5 kB (A) (operating), < 3.4 B(A) (idle) Power Consumption 35 W (printing), < 11 W (ready), < 3.5 W (sleep), < 0.1 W (standby), Auto-scheduled printer on/off usage.	Interfaces	Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n
drivers, printing support for Chrome OS, print from USB pen drive Raster driver for macOS and Windows, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility. TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, quide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enable Yes One-click multi-size printing Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5 88 ((printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Native print languages	
Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and mac0S, HP Support Assistant for Windows, HP Smart for Windows, mac0S, Android, and i0S Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		Wi-Fi Direct, remote printing, Apple AirPrint and HP Smart app for Android and iOS devices, Windows and macOS printer
Dimensions (W x D x H) Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and mac0S, HP Support Assistant for Windows, HP Smart for Windows, mac0S, Android, and i0S Remote print enabled Ves One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Drivers	Raster driver for macOS and Windows, HP-GL/2 driver for Windows
Printer 1407 x 701 x 967 mm Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Security features	
Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enable Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Dimensions (W x D x H)	
Shipping 1575 x 570 x 650 mm Weight Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage.	Printer	1407 x 701 x 967 mm
Printer 60 kg Shipping 83.5 kg What's in the box HP DesignJet TB50 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Shipping	
Shipping 83.5 kg What's In the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Weight	
Shipping 83.5 kg What's In the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Printer	60 kg
What's in the box HP DesignJet T850 MFP, printheads, ink cartridges, printer stand, spindle, guide, poster, warranty flyer, power cord HP Software and solutions HP Click for Windows and macOS, HP Support Assistant for Windows, HP Smart for Windows, macOS, Android, and iOS Remote print enabled Yes One-click multi-size printing Yes Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating, <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		
HP Software and solutions Remote print enabled Ves One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		
One-click multi-size printing Ves Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	HP Software and solutions	
Environmental ranges Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Remote print enabled	Yes
Recycled plastic in printer 37% Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	One-click multi-size printing	Yes
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Environmental ranges	
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Recycled plastic in printer	37%
Operating humidity 20 to 80% RH Operating altitude Up to 3000 m Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		5 to 40°C
Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		20 to 80% RH
Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.	Operating altitude	Up to 3000 m
Acoustics Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		
Sound pressure 42 dB(A) (operating), <16 dB(A) (idle) Sound power 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		_
Sound power 5.8 B(A) (operating), < 3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		42 dB(A) (operating), <16 dB(A) (idle)
Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		· · · · ·
Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Auto-scheduled printer on/off usage.		
		35 W (printing) < 11 W (ready) < 3.5 W (sleep) < 0.1 W (standby) Auto-scheduled printer on/off usage
input mage toute rangings. Too E to 1 (= rong), 20/00 TE (22 TE), LE MIIIA		
	- 4	error and the control of the control

Certification

Safety	USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)
Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC)
Environmental	ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements.
Warranty	Two-year limited hardware warranty. Warranty and support options vary by

Ordering information

Original HP printing supplies

498N0A	HP 739 DesignJet Printhead Replacement Kit
498N4A	HP 738 130-ml Black DesignJet Ink Cartridge
498N5A	HP 738 130-ml Cyan DesignJet Ink Cartridge
498N6A	HP 738 130-ml Magenta DesignJet Ink Cartridge
498N7A	HP 738 130-ml Yellow DesignJet Ink Cartridge
498N8A	HP 738 300-ml Black DesignJet Ink Cartridge
676M6A	HP 738 300-ml Cyan DesignJet Ink Cartridge
676M7A	HP 738 300-ml Magenta DesignJet Ink Cartridge
CZCMOA	LID 730 300 I Velle Bester let let Centrides

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/Original HPinks.

Original HP large format printing materials

HP Universal Bond Paper (FSC® certified)⁴ (recyclable)⁵ HP Coated Paper (FSC® certified)⁴ (recyclable)⁵ HP Heavyweight Coated Paper (FSC® certified)⁴ (recyclable)⁵

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U56RSE HP 3-year Next Business Day HW Support U56RTE HP 4-year Next Business Day HW Support U56RVE HP 5-year Next Business Day HW Support

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

 $^{1}\,\text{Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper}$

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Pape (bond) and Original HP inks.
² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.
³ With HP Universal Instant Dry Photo Gloss media with Original HP inks.
³ BMG trademark license code FSC®-C115319, see http://www.fsc.org . HP trademark license code FSC®-C107543, see http://www.fsc.org
⁵ Can be recycled through commonly available recycling programs.

For more information, contact your HP Amplify Synergy Partner...



hello@colyer.co.uk | 01483 596200 | www.colyer.co.uk

















