# Apeos C4030 / C3530 Functions & Specifications

# Colyer.

#### Basic Specifications / Copy Function

Item		Description	
		Apeos C4030	Apeos C3530
Туре		Desktop	
Memory (	Capacity	4 GB (Max: 4 GB)	
Storage D Capacity*		128 GB	
Color Cap	ability	Full Color	
Scan Reso	olution	600 x 600 dpi	
Printing R	tesolution	1,200 x 2,400 dpi	
Warm-up	Time*2	33 seconds or less (23 degrees Celsius room temperature)	
Recovery Time (Recovery Time from Sleep Mode)			
Original Size		Maximum of A4, Letter, Legal*3 for both Sheet and Book	
	Max	A4, Letter, Legal	
Paper	Min	A6*4 [64 x 127 mm when using Bypas	s Tray]
Size	Image loss width	Lead edge 4.0 mm, Trail edge 4.0 mm, Right/Left edge 4.0 mm	
D	Paper Tray	60 to 220 gsm / 16 lb. bond to 122 lb. index	
Paper Weight*5	Bypass Tray	60 to 220 gsm / 16 lb. bond to 122 lb. index	
First Copy	/ Output	B/W: 7.5 sec. (Letter / A4, Monochron	ne priority mode)
Time	•	Color: 8.0 sec. (Letter / A4, Color priority mode)	
Continuo	us Copy	B/W: 42 ppm (Letter) / 40 ppm (A4)	B/W: 37 ppm (Letter) / 35 ppm (A4)
Speed *6		Color: 42 ppm (Letter) / 40 ppm (A4)	Color: 37 ppm (Letter) / 35 ppm (A4)
Paper Tray	Standard	Standard Tray: 550 sheets Bypass Tray: 150 sheets	
Capacity*7		550-Sheet Feeder: 550 sheets	
	Max	2,350 sheets [Standard + 550-Sheet Feeder x 3]	
Output Tra	y Capacity*7	250 sheets	
Power Su	pply	AC220-240 V +/- 10 %, 8 A, 50/60 Hz common	
Maximum Power Consumption		1,270 W (AC220 V +/- 10 %), 1,450 W (AC240 V +/- 10 %) Sleep Mode: 0.4 W (AC230 V) Low Power Mode: 11 W (AC230 V) Ready Mode: 83 W (AC230 V)	
Dimensions		W 470 x D 500*8 x H 582 mm / W 18.5 x D 19.7 x H 23.0"	W 420 x D 500*8 x H 565 mm / W 16.6 x D 19.7 x H 22.3"
Weight*9		35 kg / 78 lb.	34 kg / 75 lb.
*1: The St	orage Device	Capacity is not totally available for cus	stomers.

- \*1: I he Storage Device Capacity is not totally available for customers.

  \*2: It may change depending on usage conditions.

  \*3: For Apeos C3530, the Legal size reading is from the Duplex Automatic Document Feeder.

  \*4: When using A6 size paper with the Standard Tray, the optional A5 LEF / A6 Tray Guide is required.

  \*5: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement.
- \*6: The speed may be reduced due to the image quality adjustment \*7: 80 gsm paper.
- \*8: The motor part of Duplex Automatic Document Feeder rear is included.
  \*9: Including Toner Cartridge.

#### Print Function

Item		Description	
Туре		Built-in type	
Paper Size	Max	A4, Letter, Legal [215.9 x 520 mm when using Bypass Tray]	
	Min	A6*1 [64 x 127 mm when using Bypass Tray]	
	Image loss width	Lead edge 4.0 mm, Trail edge 4.0 mm, Right/Left edge 4.0 mm	
Continuous Print Speed*2		Same as the Basic Specifications / Copy Function	
Printing Resolution	Standard	[PCL Driver] Standard: 1,200 x 2,400 dpi, High Quality: 1,200 x 2,400 dpi, High Resolution: 1,200 x 1,200 dpi	
	Optional	[Adobe® PostScript® 3™ Driver] High Speed (Standard): 600 x 600 dpi, High Quality: 1,200 x 2,400 dpi, High Resolution: 1,200 x 1,200 dpi	
Page	Standard	PCL5 / PCL6	
Description Language	Optional	Adobe® PostScript® 3™	
Supported Operating System* <sup>3</sup>	Standard	[PCL Driver] Windows 11 (64 bit) / Windows 10 (32 bit / 64 bit) / Windows Server 2022 (64 bit) / Windows Server 2019 (64 bit) / Windows Server 2016 (64 bit) [Mac OS X Driver] macOS 14 / 13 / 12 / 11 / 10.15	
	Optional	[Adobe® PostScript® 3™ Driver] Windows 11 (64 bit) / Windows 10 (32 bit / 64 bit) / Windows Server 2022 (64 bit) / Windows Server 2019 (64 bit) / Windows Server 2016 (64 bit) macOS 14 / 13 / 12 / 11 / 10.15	
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0	
interface	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)	

Note: XPS stands for XML Paper Specification.

- \*1: When using A6 size paper with the Standard Tray, the optional A5 LEF / A6 Tray Guide is required.
  \*2: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document.
  \*3: Please refer to our official website for the latest supported OS.

#### Scan Function

Item		Description
Туре		Color Scanner
Original Size		Same as the Basic Specifications / Copy Function
Scan Resolution		600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi
Scan Speed		Same as the Scan Speed for the Duplex Automatic Document Feeder
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T
	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)

#### Fax Function (Optional)

Item	Description
Original Size	Max: A4, Legal
Recording Paper Size	Max: A4, Legal; Min: A5
Transmission Time	2 seconds and more but fewer than 3 seconds*1
Transmission Mode	ITU-T G3
Applicable Lines	Telephone subscriber line, PBX, Maximum 1 port*2 (G3-1 port)

- \*1: For Apeos C3530, the Legal size reading is from the Duplex Automatic Document Feeder.
- \*2: When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

# **Duplex Automatic Document Feeder**

Item		Description	
		Apeos C4030	Apeos C3530
Original Size / Paper Weight		Max: A4, Letter, Legal; Min: A5*1	
		60 to 128 gsm / 16 lb. bond to 34 lb. bond (In Duplex: 60 to 128 gsm)	
Capacity*2		100 sheets	50 sheets
Scan Speed*3	Сору	B/W: 42 ppm (Letter), 40 ppm (A4)	B/W: 37 ppm (Letter), 35 ppm (A4)
	(Simplex)	Color: 42 ppm (Letter), 40 ppm (A4)	Color: 37 ppm (Letter), 35 ppm (A4)
		B/W: 53 ppm, Color: 53 ppm	B/W: 48 ppm, Color: 48 ppm
	Scan	(1 pass, 2 sided scanning; B/W and Color 105ppm) [Standard Document (A4), 200 dpi, to Folder.]	(1 pass, 2 sided scanning; B/W and Color 96ppm) [Standard Document (A4), 200 dpi, to Folder.]

- 1: The minimum custom size is 139.7 x 139.7 mm.
- \*2: 80 gsm paper. \*3: The scanning speed varies depending on the documents.

### 550-Sheet Feeder (Optional)

330 Sheet recael (Optional)		
Item	Description	
Paper Size	Max: A4, Letter, Legal Min: A5 Custom Size: 76.2 x 190.5 mm to 215.9 x 355.6 mm	
Paper Weight	60 to 220 gsm / 16 lb. bond to 122 lb. index	
Feeding Capacity*1 / Number of Tray*2	550 sheets x 1-tray	
Dimensions	W 420 x D 465 x H 123*3 mm / W 16.6 x D 18.4 x H 4.9"	
Weight	6.6 kg / 15 lb.	

- \*1: 80 gsm paper. \*2: Up to 3 trays can be added.
- \*3: When excluding installing connections.

# Caster (Optional)

Item	Description
Dimensions*1	W 725 x D 773 x H 90*2 mm / W 28.6 x D 30.5 x H 3.6"*2
Weight	12.6 kg / 28 lb.

- \*1: Including the foot part.
- \*2: When excluding installing connections.

# Cabinet (Optional)

Item	Description
Dimensions*1	W725 x D773 x H 336°2 mm / W 28.6 x D 30.5 x H 13.3"°2 (Inside Dimension: W 360 x D 415 x H 200 mm / W 14.2 x D 16.4 x H 7.9")
Weight	23.8 kg / 53 lb.

- \*1: Including the foot part.
- \*2: When excluding installing connections.

If the storage media of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall the Company be liable for any damages whatsoever arising from loss of data.

Functional spare parts will be available for at least 7 years after the product is no longer manufactured.